

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings of claims in the application:

Listing of Claims

1. (Withdrawn) An assay device, comprising an array having both a planar surface and a configuration of reaction loci thereon, with each of said loci consisting essentially of at least one peptide or protein at least substantially suspended or dissolved in a hydrophilic carrier for said peptide or protein.
2. (Withdrawn) The assay device of claim 1, wherein said planar surface further comprises a nonporous chip or slide.
3. (Withdrawn) The assay device of claim 1, wherein said nonporous chip or slide includes a component selected from the group consisting of silicon; glass; silica; quartz; polystyrene and polyalkylene polymer.
4. (Withdrawn) The assay device of claim 1, wherein said configuration of reaction loci is that of a rectangular grid.
5. (Withdrawn) The assay device of claim 1, wherein said hydrophilic carrier is selected from the group consisting of saccharides, alkylene diols and alkylene polyols and said reaction loci measure between about 10 and 250 micrometers.

6. (Withdrawn) The assay device of claim 1, wherein said hydrophilic carrier is selected from the group consisting of dextran; pluronic acid; carbohydrates of the pentose; ribose or hexose families; polysaccharides; polyethylene glycol polymer; 1,2-ethanediol; 2,3-butanediol and 1,2,3-propanetriol (glycerol), and said reaction loci measure between about 50 and 100 micrometers.

7. (Withdrawn) The assay device of claim 1, wherein said reaction loci further comprises enzyme reaction components selected from the group consisting of cofactors; inhibitors; antibodies; activators and buffer elements.

8. (Withdrawn) The assay device of claim 1, wherein said reaction loci includes a biological molecule or fraction selected from the group consisting of proteins; peptides; nucleic acids; enzymes; antibodies; lipids; cell lysates and vesicles.

9. (Withdrawn) The assay device of claim 1, wherein said loci further comprises fluorogenic substrates, chromogenic substrates or other reporter substrates.

10. (Currently Amended) An assay system, comprising:
a set of operating instructions resident in computer software;
a first set of computer-controlled reactant dot applicators;
a second, separate computer-controlled device for biological sample aerosol generation;
a computer-controlled xy positioner;
a computer and operating software; and

a chamber for control of biological samples,

wherein the first set of computer-controlled reactant dot applicators ~~create~~ creates a plurality of reaction spots having one or more constituents therein to which the aerosolized biological sample droplets are applied simultaneously by said second, separate computer-controlled device for sample aerosol generation for computer-enhanced assay of any reaction between the sample droplets and said constituents.

11. (Previously Presented) The assay system of claim 10, wherein said system contains one or more subcomponents and wherein said operating instructions send signals, via serial or parallel port, to start, to stop, to establish operating set points and to control said one or more subcomponents of the device, whereby each of said one or more subcomponents may have an internal or external standing controller or driver.

12. (Currently Amended) The ~~subcomponents~~ assay system of claim 11, wherein said one or more subcomponents further ~~comprising~~ comprises at least one device selected from the group consisting of multiple positive displacement microsyringe pumps, pressure nozzles, ultrasonic nozzles, ink-jet printheads, position-actuated ink-jet printheads, surface-actuated ink-jet printheads, fluid-contacting or fluid-noncontacting ultrasound transducers; gas flow meter/controller; xy positioner system and exhaust/filtration fan.

13. (Original) The assay system of claim 10, wherein said microsyringes hold 1.0 microliters to 1000 μ L of biological sample.

14. (Original) The assay system of claim 10, wherein said microsyringes deliver samples at a constant flow rate.

15. (Original) The assay system of claim 10, wherein said device for aerosol generation is an ultrasonic nebulizer.

16. (Withdrawn) The method for assaying a biological sample using a peptide or protein chip according to claim 1, comprising:

- a) selecting a planar surface;
- b) selecting a hydrophilic carrier and arraying a plurality of substrates in discrete reaction loci within aliquots of said hydrophilic carrier on said planar surface;
- c) applying an aerosolized or misted sample having a sample droplet size between about 5 and 15 micrometers to the array formed in step (b); and
- d) detecting any reaction between the sample and the plurality of substrates.

17. (Withdrawn) A method for assaying a biological sample using a peptide or protein chip according to claim 1, comprising applying an aerosolized or misted sample onto said configuration of reaction loci and detecting any reaction between any constituents of the sample and said peptide or protein contained within said configuration of reaction loci.

18. (Withdrawn) A method for assaying a biological sample using a peptide or protein chip according to claim 1, comprising applying an aerosolized or misted sample onto said configuration of reaction loci using an ultrasonic nebulizer and detecting any reaction between any constituents of the sample and said peptide or protein contained within said configuration of reaction loci.